


SECTION 1: Identification

Product identifier	
Product name	Phenolphthalein Indicator
Product number	R-0638; R-0638-PL; R-0638BR; R-0638BR-PL; R-0638G; R-0638G-PL; R-0638O; R-0638O-PL; R-0638W; R-0638W-PL; R-7638
Recommended use and restrictions	Water analysis. To be used in accordance with manufacturer instructions or under the direct guidance of the manufacturer.
Manufacturer	Taylor Water Technologies LLC 31 Loveton Circle Sparks, MD 21152 Local: (410) 472-4340 – 8am – 5pm EST Toll-free: (800) 837-8548 – 8am – 5pm EST
Emergency phone number	
CHEMTREC, United States	1-800-424-9300 – 24-hour service
CHEMTREC, International	+1 703-741-5970 – 24-hour service

SECTION 2: Hazard(s) identification

Physical hazards	Flammable liquids	Category 2
Health hazards	Eye damage/irritation	Category 2A
	Carcinogenicity	Category 1B
	Germ cell mutagenicity	Category 2
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3
Environmental hazards	Not currently regulated by OSHA. For additional information, refer to section 12 of the SDS.	
Label elements		
Hazard pictograms		
Signal word	Danger	
Hazard statements	Highly flammable liquid and vapor. Causes serious eye irritation. May cause cancer. Suspected of causing genetic defects. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness.	
Precautionary statements		
Prevention	Keep away from heat/sparks/open flames/hot surfaces. -No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist or vapor. Wash skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Use only outdoors or in a well-ventilated area.	
Response	<p>IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. IF EYE IRRITATION PERSISTS: Get medical advice/attention.</p> <p>IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a physician or poison center if you feel unwell.</p> <p>IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water.</p> <p>IF EXPOSED OR CONCERNED: Get medical advice/attention.</p> <p>IN CASE OF FIRE: Use alcohol-resistant foam, carbon dioxide, dry chemical powder, or water fog to extinguish.</p>	

Storage	Store locked up. Store in well-ventilated place. Keep cool. Keep tightly capped. Store out of direct sunlight between 36°F-85°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazards not otherwise classified Not applicable

SECTION 3: Composition/information on ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	% w/w
Water	Dihydrogen oxide	7732-18-5	45-70
Isopropyl alcohol	Isopropanol	67-63-0	30-60
Phenolphthalein	3,3-Bis(4-hydroxyphenyl)-1(3H)-isobenzofuranone	77-09-8	0.1-1

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4: First-aid measures

If inhaled

Remove individual to fresh air. Seek medical advice/attention if breathing becomes difficult or if respiratory irritation develops. Give oxygen or artificial respiration if needed.

In case of skin contact

Immediately flush skin with plenty of water for at least 20 minutes. If clothing comes in contact with the product, the clothing should be removed and laundered before reuse. Seek medical advice/attention if irritation develops.

In case of eye contact

Immediately flush eyes with plenty of water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If symptoms persist or in all cases of concern, seek medical advice/attention.

If swallowed

Immediately call a physician or poison control center. Rinse mouth. Never give anything by mouth to a person who is unconscious or is having convulsions. Do NOT induce vomiting unless directed by physician. If vomiting occurs, keep head low so that stomach content does not get into the lungs. If symptoms persist or in all cases of concern, seek medical advice/attention.

Most important symptoms and effects, both acute and delayed

Direct skin or eye contact may cause irritation. Symptoms may include redness or itching. Tearing of the eyes or blurred vision may occur. Inhalation may cause headache, drowsiness, or dizziness. Ingestion may cause gastrointestinal irritation, nausea, vomiting, and diarrhea. This product contains material that may be carcinogenic to humans and is suspected of causing genetic defects, damaging fertility, or possible risk to the unborn child.

Refer to section 11 of the SDS for delayed and immediate effects and chronic effects from short- and long-term exposure.

Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically.

General information

Ensure medical personnel are aware of the material(s) involved and take precautions to protect themselves.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media	Alcohol-resistant foam, carbon dioxide, dry chemical powder, or water fog.
Unsuitable extinguishing media	Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Specific hazards arising from the substance or mixture

Fire hazard	Flammable liquid and vapor. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can be electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential static discharge, use proper bonding and grounding procedures. This material may be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, or mechanical/electrical equipment). Vapors are heavier than air and may spread along floors.
Explosion hazard	Vapors may form explosive mixtures with air. This material may be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, or mechanical/electrical equipment). Vapors are heavier than air and may spread along floors.
Reactivity	Hazardous reactions will not occur under normal conditions.
Hazardous combustion products	Carbon oxides, nitrogen oxides.

Advice for firefighters

Precautionary measures Exercise caution when fighting any chemical fire; hazardous fumes will be present.

Firefighting equipment/instructions	Use water spray or fog for cooling exposed containers.
Protection during firefighting	Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	Refer to section 9 of the SDS for flammability properties.

SECTION 6: Accidental release measures

Personal precautions, protective equipment, and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during cleanup. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protective equipment, refer to section 8 of the SDS.

Environmental precautions

Avoid discharge into drains, watercourses, or onto the ground.

Methods and material for containment and cleaning up

Ventilate the contaminated area. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Dike the spilled material where this is possible. Stop leak if it can be done without risk. Absorb spillage to prevent material damage. Absorb in vermiculite, dry sand or earth, and place into containers. Prevent entry into waterways, sewers, basements, or confined areas. Following product recovery, flush area with water to remove residual contamination. Never return spills to original containers for reuse. Contaminated absorbent material may pose the same hazards as the spilled product. In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Reference to other sections

For exposure controls and personal protection, refer to section 8 of the SDS. For waste disposal, refer to section 13 of the SDS.

SECTION 7: Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Vapors may form explosive mixtures with air. Keep away from sources of ignition. NO SMOKING. Do not handle, store, or open near an open flame, sources of heat or sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist or vapor. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. For personal protective equipment, refer to section 8 of the SDS. Keep away from incompatibles. Observe good industrial hygiene practices. Label containers appropriately.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in well-ventilated place. Keep cool. Keep tightly capped. Store out of direct sunlight between 36°F-85°F. Store away from incompatible materials (refer to section 10 of the SDS).

SECTION 8: Exposure controls/personal protection

Occupational exposure limits

US ACGIH Threshold Limit Values

Components	Type	Value
Isopropanol (CAS 67-63-0)	STEL	400 ppm (980 mg/m ³)
Isopropanol (CAS 67-63-0)	TWA	200 ppm (492 mg/m ³)

US NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Isopropanol (CAS 67-63-0)	ST	500 ppm (1225 mg/m ³)
Isopropanol (CAS 67-63-0)	TWA	400 ppm (980 mg/m ³)
Isopropanol (CAS 67-63-0)	IDLH	2000 ppm (4920 mg/m ³)

US OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Isopropanol (CAS 67-63-0)	PEL	400 ppm (980 mg/m ³)

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Isopropanol (CAS 67-63-0)	40 mg/L	Acetone	Urine	End of shift at end of workweek

Exposure controls

Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eyewash facilities and emergency shower must be available when handling this product.
Personal protective equipment	
Eye/face protection	Wear appropriate chemical safety goggles if contact is likely to occur.
Skin protection	Wear appropriate chemical-resistant gloves and clothing if contact is likely to occur.
Body protection	Wear appropriate protective clothing if contact is likely to occur.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fumes at levels exceeding the exposure limits. Advice should be sought from respiratory protection suppliers.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state	Liquid
Form	Liquid
Color	Clear colorless
Odor	Alcohol
Odor threshold	90 mg/m ³
pH	No data available
Evaporation rate	No data available
Melting point	No data available
Freezing point	No data available
Initial boiling point (boiling range)	180°F (82°C)
Flash point	53°F (12°C) Closed cup
Specific gravity	0.93
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability (solid, gas)	Flammable
Upper Flammability Limit	UEL 12% v/v 200° F (93°C)
Lower Flammability Limit	LEL 2% v/v 200° F (93°C)
Vapor pressure	No data available
Vapor density	No data available
Relative density	0.93 g/mL at 22°C
Solubility	Soluble in water
Partition coefficient (n-octanol/water)	No data available
Viscosity	No data available
Explosive properties	Moderately explosive when exposed to heat or flame.
Oxidizing properties	Not oxidizing

SECTION 10: Stability and reactivity

Reactivity	Hazardous reactions will not occur under normal use, storage, and transport.
Chemical stability	Stable under recommended handling and storage conditions (refer to section 7 of the SDS).
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Heat, sparks, open flames, and other ignition sources. Temperatures exceeding the flash point. Direct sunlight. Contact with incompatible materials. Do not use in areas without adequate ventilation.
Incompatible materials	Strong acids. Strong oxidizing agents. Acetaldehyde, chlorine, ethylene oxide, isocyanates.
Hazardous decomposition products	No hazardous decomposition products known.

SECTION 11: Toxicological information

Information on likely routes of exposure

Inhalation	Avoid inhalation of this product. Use in a well-ventilated area.
Skin contact	Direct contact with skin may cause temporary irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Avoid accidental ingestion by observing good hygiene practices. Wash hands thoroughly after handling this product.

Symptoms related to the physical, chemical, and toxicological characteristics

This product contains material that may be carcinogenic to humans, based on sufficient evidence of carcinogenicity from studies in experimental animals, and is suspected of causing genetic defects, damaging fertility or possible risk to the unborn child.
Refer to section 4 of the SDS for most important symptoms and effects.

Delayed and immediate effects and chronic effects from short- and long-term exposure

Acute toxicity	This product is not classified as an acute toxicity hazard.
Skin corrosion/irritation	No data available
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory sensitization	No data available
Skin sensitization	No data available
Germ cell mutagenicity	Suspected of causing genetic defects.
Carcinogenicity	May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Phenolphthalein; Group 2B-Possibly carcinogenic to humans

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096)

Not regulated

US National Toxicology Program (NTP) Report on Carcinogens

Phenolphthalein; Reasonably anticipated to be a human carcinogen

Reproductive toxicity	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	No data available
Aspiration hazard	No data available

SECTION 12: Ecological information

Ecotoxicity	This product is not classified as environmentally hazardous.
Persistence and degradability	No data available
Bioaccumulative potential	No data available
Mobility in soil	No data available
Other adverse effects	Large or frequent spills can have a harmful or damaging effect on the environment.

SECTION 13: Disposal considerations

Collect and reclaim or dispose of in sealed containers at a licensed waste disposal site. Since emptied containers may retain product residue, follow label warnings even after container is emptied. This material and its container must be disposed of in a safe manner. Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

DOT

UN number	1219
UN Proper shipping name	Isopropyl alcohol solution
Reportable Quantity	None
Class (Subsidiary risk)	3
Label(s)	3
Packing group	II
Special provisions	IB2, T4, TP1
Packaging exceptions	4b, 150

Packaging, non-bulk 202

IATA

UN number 1219
UN Proper shipping name Isopropyl alcohol solution
Class (Subsidiary risk) 3
Packing group II
Special provisions A180

IMDG

UN number 1219
UN Proper shipping name Isopropyl alcohol solution
Class (Subsidiary risk) 3
Packing group II
Environmental hazards
Marine pollutant No
Special provisions None
EmS F-E, S-D

Special precautions for user Read safety instructions, SDS, and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code This substance/mixture is not intended to be transported in bulk.

DOT hazard pictograms



IATA; IMDG hazard pictograms



SECTION 15: Regulatory information

US federal regulations

CERCLA Hazardous Substance (40 CFR 302.4)

Not regulated

SARA 302 Extremely Hazardous Substance (40 CFR 355 Appendices A / B)

Not regulated

SARA 304 Emergency Release Notification

Not regulated

SARA 311/312 Hazardous Chemical

<u>Chemical name</u>	<u>CAS number</u>
Isopropanol	67-63-0
Phenolphthalein	77-09-8

SARA 313 (TRI reporting)

<u>Chemical name</u>	<u>CAS number</u>
Phenolphthalein	77-09-8

TSCA Section 8(b) Chemical Inventory

All components are on the U.S. EPA TSCA Inventory list.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs)

Not regulated

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated

Clean Water Act, Toxic and Priority Pollutants (40 CFR 401.15 and CFR 423, Appendix A)

Not regulated

Safe Drinking Water Act (SDWA)

Not regulated

US state regulations

California Safe Drinking Water and Toxic Enforcement Act of 1986 (California Proposition 65)

<u>Chemical name</u>	<u>CAS number</u>
Phenolphthalein	77-09-8

WARNING: This product can expose you to phenolphthalein, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

Massachusetts Right-to-Know Act

<u>Chemical name</u>	<u>CAS number</u>
Isopropanol	67-63-0

New Jersey Worker and Community Right-to-Know Act

<u>Chemical name</u>	<u>CAS number</u>
Isopropanol	67-63-0
Phenolphthalein	77-09-8

Pennsylvania Worker and Community Right-to-Know Act

<u>Chemical name</u>	<u>CAS number</u>
Isopropanol	67-63-0

Rhode Island Right-to-Know Act

<u>Chemical name</u>	<u>CAS number</u>
Isopropanol	67-63-0

SECTION 16: Other information

NFPA Rating

Health hazard	2
Fire hazard	3
Reactivity	0
Specific	N/A

Disclaimer

The information in the Safety Data Sheet is offered for your consideration and guidance for safe handling, use, storage, transportation, disposal, and release of this product and is not considered a warranty or quality specification. Taylor Water Technologies LLC disclaims all expressed or implied warranties and assumes no responsibility for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

License granted to make unlimited paper copies for internal use only. This Safety Data Sheet may not be altered in any way without the expressed knowledge and permission of Taylor Water Technologies LLC. The information contained in this sheet is based on lab experience and the most current data available.

Issue date:

May 2015

Revision date:

04/06/2022

Revision information:

This document embodies significant change(s) that may impact classification, safe handling, or health information for the associated product(s). The information contained herein should be reviewed in its entirety before handling material.

Identification: Manufacturer information and emergency phone number

First aid: Most important symptoms and effects, both acute and delayed

Toxicological information: Information on likely routes of exposure

Supersedes revision dated April 2020.